



### 27" WQHD monitor with IPS panel and height adjustable stand

An eye catching 3-side borderless design makes the ProLite XUB2793QS perfect for multi-monitor setups. The IPS panel and WQHD (2560x1440) resolution, offer both excellent colour performance and viewing angles, noticeably sharper images, which is ideal for productivity solutions, demanding office, and financial applications. Featuring a 1ms response time, and FreeSync, this is suitable for the home office environment and casual gaming.

Equipped with speakers, headphone socket, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue and an ergonomic 150mm height adjustable stand for optimal user comfort, make this 27" XUB2793QS display is ideal for any workplace.



#### IPS Technology

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.



#### WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.

## 01 DISPLAY CHARACTERISTICS

Design	3-side borderless
Diagonal	27", 68.5cm
Panel	IPS panel technology LED, matte finish
Native resolution	2560 x 1440 @75Hz (DisplayPort&HDMI, 3.7megapixel WQHD)
Aspect ratio	16:9
Panel brightness	300 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 96%; NTSC: 72%)
Horizontal Sync	30 - 120kHz
Viewable area W x H	596.7 x 335.7mm, 23.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 DisplayPort x1
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
FreeSync support	yes
Extra	i-style Colour
OSD languages	EN, DE, FR, IT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu, + / Volume, - / Eco, Input Select/ Exit
User controls	picture (brightness, contrast, black tuner, sharpness, overdrive, ACR, Eco, X-res technology, MBR), colour (warm, normal, cool, user colour, i-Style colour, gamma), input select, audio (volume, mute), language, OSD settings (OSD H. position, OSD V. position, OSD background, OSD rotate, OSD time out, information), setup menu (video mode adjust, HDMI RGB range, blue light reducer, DDC/CI, Adaptive Sync, opening logo, LED), reset
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

## 05 ACCESSORIES INCLUDED

Cables	power, HDMI
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	25W typical, 0.5W stand by, 0.5W off mode

## 07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
REACH SVHC	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	612.5 x 399 (549) x 209.5mm
Box dimensions W x H x D	688 x 435 x 155mm
Weight (without box)	6.2kg
Weight (with box)	7.7kg
EAN code	4948570118946



*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED