

PURELL® Hand sanitising gel VF481™

Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015					
SECTIO	SECTION 1: Identification of the substance/mixture and of the company/undertaking							
1.1 Prod	uct identifier							
Trac	de name	: PURELL® Ha	nd sanitising gel VF481™					
1.2 Relev	vant identified uses of	the substance or n	nixture and uses advised against					
	Use of the Sub- : Hand Sanitizer stance/Mixture							
1.3 Deta	ils of the supplier of the	e safety data sheet						
Company : GOJO Industries-Europe Ltd. Units 5 & 6, Stratus Park MK10 0DE Brinklow, Milton Keynes								
Tele	ephone	: +44(0) 19085	88444					
Tele	əfax	: +44(0) 19085	88445					
	ail address of person oonsible for the SDS	: infoUK@gojo	com					
1.4 Emergency telephone number +44(0) 8445605135								
SECTIO	N 2: Hazards identifi	cation						

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12 Flammable liquids, Category 3	72/2008) H226: Flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting ef- fects.
Classification (67/548/EEC, 1999/45/EC) Flammable	R10: Flammable.
Irritant	R36: Irritating to eyes.
Dangerous for the environment	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environ-ment.



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
2.2 Label	elements		
Labe	lling (REGULATION (EC) No 1272/2008)	
Haza	rd pictograms		!
Signa	al word	: Warning	
Haza	rd statements	: H226 H319 H412	Flammable liquid and vapour. Causes serious eye irritation. Harmful to aquatic life with long lasting ef- fects.
Preca	autionary statements	: Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P233	Keep container tightly closed.
		P273 P280	Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P303 + P361 -	 P353 IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water/shower.
		P337 + P313	If eye irritation persists: Get medical advice/ attention.

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Ethanol	64-17-5 200-578-6	F; R11 Xi; R36	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50 - < 70
Propan-2-ol	67-63-0 200-661-7	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 10
Copper Gluconate	527-09-3 208-408-2	Xn; R22 N; R50/53	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0.025 - < 0.1



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03. Date of first issue: 13.01.						
			H410						
Fo	For explanation of abbreviations see section 16.								
SECTI	SECTION 4: First aid measures								
4.1 Des	cription of first aid mea	sures							
General advice : In the case of accident or if you feel unwell, seek me vice immediately. When symptoms persist or in all cases of doubt seel advice.									
Pro	ptection of first-aiders	and use the re	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.						
lf iı	nhaled		If inhaled, remove to fresh air. Get medical attention if symptoms occur.						
In case of skin contact : Wash with water and soap as a precaution. Get medical attention if symptoms occur.									
In case of eye contact : In case of contact, immediately flush eyes with ple for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.				ith plenty of water					
lf s	wallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.							
4.2 Mos	st important symptoms	and effects, both ac	cute and delayed						
Ris		: Causes seriou	•						
4.3 Indi	cation of any immediate	e medical attention	and special treatment need	ed					
	eatment		natically and supportively.						

SECTION 5: Firefighting measures

5.1	5.1 Extinguishing media							
	Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical					
	Unsuitable extinguishing media	:	High volume water jet					



Vers 2.0	ion	Revision Date: 03.06.2015		SDS Number: 7574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015			
5.2 \$	5.2 Special hazards arising from the substance or mixture							
Specific hazards during fire- fighting		:	 Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapours may form explosive mixtures with air. Exposure to combustion products may be a hazard to health. 					
Hazardous combustion prod- ucts		:	Carbon oxides					
5.3	Advice	for firefighters						
Special protective equipment for firefighters		:		e, wear self-contained breathing apparatus. tective equipment.				
Specific extinguishing meth- ods		:	cumstances and t Use water spray t	measures that are appropriate to local cir- he surrounding environment. o cool unopened containers. ged containers from fire area if it is safe to do				

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
6.2 Environmental precautions	
Environmental precautions	 Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	: Non-sparking tools should be used.
	Soak up with inert absorbent material.
	Suppress (knock down) gases/vapours/mists with a water spray jet.
	For large spills, provide dyking or other appropriate contain- ment to keep material from spreading. If dyked material can
	be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-
	bent.
	l ocal or national regulations may apply to releases and dis-

Local or national regulations may apply to releases and dis-



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
		employed in the mine which reg Sections 13 an	aterial, as well as those materials and items e cleanup of releases. You will need to deter- ulations are applicable. d 15 of this SDS provide information regarding national requirements.
See s	ence to other sections ections: 7, 8, 11, 12 an	d 13.	
	7: Handling and st	-	
	utions for safe handlir nical measures	: See Engineerin	ng measures under EXPOSURE ERSONAL PROTECTION section.
Local	/Total ventilation		exhaust ventilation. area equipped with explosion proof exhaust
Advic	e on safe handling	Do not swallow Do not get in ey Avoid prolonge Handle in acco practice. Non-sparking to Keep container Keep away fror Take precautio	ves. d or repeated contact with skin. rdance with good industrial hygiene and safety pols should be used.
Hygie	ne measures	located close to	e flushing systems and safety showers are the working place. When using do not eat, Wash contaminated clothing before re-use.
7.2 Condi	tions for safe storage,	, including any inco	mpatibilities
	irements for storage and containers	Keep in a cool,	ly labelled containers. Keep tightly closed. well-ventilated place. Store in accordance with ational regulations. Keep away from heat and ion.
Advic	e on common storage	Strong oxidizin Organic peroxi Flammable soli Pyrophoric liqu Pyrophoric soli Self-heating su	des ds ds bstances and mixtures d mixtures, which in contact with water, emit



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
		Explosives Gases	
-	f ic end use(s) ific use(s)	: No data availabl	e

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Ethanol	64-17-5	OELV - 15 min (STEL)	1,000 ppm	IE OEL		
Propan-2-ol	67-63-0	OELV - 8 hrs (TWA)	200 ppm	IE OEL		
Further information		Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body				
	OELV - 15 min 400 ppm IE OEL (STEL)					
Further information	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body					

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Ethanol	 End Use: Workers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 1900 mg/m3 End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 343 mg/kg bw/day End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 950 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 950 mg/m3 End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 950 mg/m3 End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 206 mg/kg bw/day End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 206 mg/kg bw/day End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 206 mg/kg bw/day End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 114 mg/m3 End Use: Consumers Exposure routes: Inhalation
	• •



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
Propa	n-2-ol	Value: 87 mg/k : End Use: Worke Exposure routes Potential health Value: 500 mg/ End Use: Worke Exposure routes Potential health Value: 888 mg/ End Use: Consu Exposure routes Potential health Value: 89 mg/m End Use: Consu Exposure routes Potential health Value: 319 mg/ End Use: Consu Exposure routes Potential health Value: 319 mg/ End Use: Consu	ers s: Inhalation effects: Long-term systemic effects /m3 ers s: Skin contact effects: Long-term systemic effects /kg bw/day umers s: Inhalation effects: Long-term systemic effects n3 umers s: Skin contact effects: Long-term systemic effects /kg bw/day umers s: Ingestion effects: Long-term systemic effects
Predie	cted No Effect Conce	ntration (PNEC) accor	ding to Regulation (EC) No. 1907/2006:
Ethan Propa		 Fresh water Value: 0.96 mg Marine water Value: 0.79 mg Intermittent use, Value: 2.75 mg Sewage treatme Value: 580 mg/ Fresh water see Value: 3.6 mg/ Marine sedimen Value: 2.9 mg/ Soil Value: 0.63 mg Oral Value: 720 mg/ Fresh water Value: 140.9 m Marine water Value: 140.9 m Sewage treatme Value: 140.9 m Sewage treatme Value: 2251 mg Fresh water see Value: 552 mg/ Marine sedimen Value: 552 mg/ Soil Value: 28 mg/k 	// /release // ent plant 1 liment kg rkg /kg g/l /release g/l ent plant g/l liment kg ut kg



Version 2.0	Revision Date: 03.06.2015		SDS Number: 574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015				
 8 2 Eve	ocuro controlo		Oral Value: 160 mg/l	kg				
-	8.2 Exposure controls							
Mir Use	Engineering measures Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.							
Per	sonal protective equip	nent						
Eye	e protection	:	Wear the following Safety goggles	g personal protective equipment:				
	nd protection Material	:	Impervious gloves Flame retardant g					
F	Remarks	:	on the concentrat stance and specif determined for the applications, we r chemicals of the a	protect hands against chemicals depending ion and quantity of the hazardous sub- ic to place of work. Breakthrough time is not e product. Change gloves often! For special ecommend clarifying the resistance to aforementioned protective gloves with the er. Wash hands before breaks and at the				
Ski	n and body protection	:	sistance data and tial. Wear the following Flame retardant a Skin contact must	e protective clothing based on chemical re- l an assessment of the local exposure poten- g personal protective equipment: Intistatic protective clothing. t be avoided by using impervious protective aprons, boots, etc).				
Re	spiratory protection	:	tilation is provided	rotection unless adequate local exhaust ven- d or exposure assessment demonstrates that thin recommended exposure guidelines.				
F	Filter type	:	Organic vapour ty	ире (А)				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear, Hazy, blue green
Odour	: alcohol-like
Odour Threshold	: No data available
рН	: 3.5 - 5.2



Ver 2.0	sion	Revision Date: 03.06.2015		DS Number: 74-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
	Malting	point/frooting point		No data available	
	weiting	point/freezing point	•	NO GALA AVAIIADIE	3
	Initial b range	oiling point and boiling	:	75.00 °C	
	Flash p	point	:	26.5 °C	
	Evapor	ation rate	:	No data available	9
	Flamm	ability (solid, gas)	:	Not applicable	
	Upper	explosion limit	:	No data available	9
	Lower	explosion limit	:	No data available	9
	Vapour	pressure	:	No data available	9
	Relativ	e vapour density	:	No data available	9
	Density	/	:	0.8850 g/cm3	
I	Solubili Wate	ity(ies) er solubility	:	soluble	
	Partitio octanol	n coefficient: n- l/water	:	Not applicable	
	Auto-ig	nition temperature	:	No data available	9
	Decom	position temperature	:	The substance of	r mixture is not classified self-reactive.
	Viscosi Visco	ty osity, kinematic	:	80 - 600 mm2/s ((20 °C)
	Explosi	ive properties	:	Not explosive	
	Oxidizii	ng properties	:	The substance of	r mixture is not classified as oxidizing.
9.2	Other ir	nformation			

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.



ersion 0	Revision Date: 03.06.2015		S Number: 4-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
0.3 Poss	sibility of hazardous	eaction	5	
Haza	rdous reactions	١	/apours may f	uid and vapour. orm explosive mixture with air. strong oxidizing agents.
0.4 Cond	ditions to avoid			
Cond	litions to avoid	: H	leat, flames a	nd sparks.
0.5 Incoi	mpatible materials			
Mater	rials to avoid	: (Dxidizing ager	ts
0.6 Haza	rdous decompositio	n produ	cts	
	azardous decompositio	•		
FCTION	N 11: Toxicological	inform	ation	
201101				
	mation on toxicologi			
Inforn expos	nation on likely routes sure		halation kin contact	
I			gestion	
		Ľ	ye contact	
Acute	e toxicity			
Not c	lassified based on ava	ilable inf	ormation.	
	ponents:			
Ethai Acute	nol: e oral toxicity	: L[D50 (Rat): > 5	,000 mg/kg
Acute	e inhalation toxicity	: L/	C50 (Rat): 124	ł.7 mg/l
			xposure time: est atmospher	
		1		
	an-2-ol: e oral toxicity	: LI	D50 (Rat): > 5	,000 mg/kg
Acute	e oral toxicity			
Acute		: L(E	C50 (Rat): 72. xposure time:	6 mg/l 4 h
Acute	e oral toxicity	: L(E	C50 (Rat): 72.	6 mg/l 4 h
Acute Acute	e oral toxicity	: L(E T	C50 (Rat): 72. xposure time:	6 mg/l 4 h re: vapour
Acute Acute Acute Copp	e oral toxicity e inhalation toxicity e dermal toxicity per Gluconate:	: L(E Ti : L)	C50 (Rat): 72. xposure time: est atmospher D50 (Rat): > 5	6 mg/l 4 h re: vapour ,000 mg/kg
Acute Acute Acute Copp	e oral toxicity e inhalation toxicity e dermal toxicity	: L(E Ti : L)	C50 (Rat): 72. xposure time: est atmospher	6 mg/l 4 h re: vapour ,000 mg/kg
Acute Acute Acute Acute	e oral toxicity e inhalation toxicity e dermal toxicity per Gluconate:	: L(E Ti : L)	C50 (Rat): 72. xposure time: est atmospher D50 (Rat): > 5	6 mg/l 4 h re: vapour ,000 mg/kg

Product:



Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

Result: No skin irritation

Components:

Ethanol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Propan-2-ol:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethanol: Species: Rabbit Method: OECD Test Guideline 405 Result: Irritation to eyes, reversing within 21 days

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product: Assessment: Does not cause skin sensitisation.

Components:

Ethanol:

Test Type: Local lymph node assay (LLNA) Exposure routes: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Exposure routes: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity


Not classified based on available information.

<u>Components:</u> Ethanol:



Version 2.0	Revision Date: 03.06.2015		DS Number: 574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
Genot	oxicity in vitro	:	Test Type: In vit Result: negative	ro mammalian cell gene mutation test
Genot	oxicity in vivo	:	Test Type: Rode Species: Mouse Application Rout Result: negative	
II Prona	n-2-ol:			
	oxicity in vitro	:	Test Type: Bacto Result: negative	erial reverse mutation assay (AMES)
Genot	oxicity in vivo	:	cytogenetic assa Species: Mouse	e: Intraperitoneal injection
	er Gluconate: oxicity in vitro	:	Test Type: Bacto Result: negative	erial reverse mutation assay (AMES)
Comp Propa Specie Applic Expos Metho	assified based on avai onents: n-2-ol: es: Rat ation Route: inhalatior ure time: 104 weeks d: OECD Test Guideli :: negative	n (vap	our)	
Repro	ductive toxicity			
-	assified based on avai	ilahle	nformation	
	onents:			
Ethan Effects	ol: s on fertility	:	Species: Mouse Application Rout	Test Guideline 416
II Propo	n-2-ol:			
	s on fertility	:	Test Type: Two- Species: Rat Application Rout Result: negative	
Effects ment	s on foetal develop-	:	Test Type: Emb Species: Rat Application Rout	ryo-foetal development e: Ingestion







Version 2.0	Revision Date: 03.06.2015		SDS Number: 574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015	
п					
То>	icity to bacteria	:	EC50 (Photobact Exposure time: 0.	erium phosphoreum): 32.1 mg/l 25 h	
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)			NOEC: 9.6 mg/l Exposure time: 9 d Species: Daphnia magna (Water flea)		
II Pro	pan-2-ol:				
То	icity to fish	:	LC50 (Pimephale Exposure time: 96	s promelas (fathead minnow)): 10,000 mg/l 6 h	
	cicity to daphnia and other atic invertebrates	:	EC50 (Daphnia m Exposure time: 24	nagna (Water flea)): > 10,000 mg/l 4 h	
То	icity to bacteria	:	EC50 (Pseudomo Exposure time: 16	onas putida): > 1,050 mg/l 6 h	
II Co	oper Gluconate:				
'	icity to fish	:	LC50 (Oncorhync Exposure time: 96	chus mykiss (rainbow trout)): 0.07 - 0.7 mg/l 6 h	
	icity to daphnia and other atic invertebrates	:	EC50 (Daphnia (v Exposure time: 48		
То	icity to algae	:	ErC50 (Scenedes - 1 mg/l Exposure time: 72	smus capricornutum (fresh water algae)): 0.1 2 h	
			NOEC (Pseudoki mg/l Exposure time: 72	rchneriella subcapitata (green algae)): 0.1 - 1 2 h	
M-F icity	Factor (Acute aquatic tox-	:	10		
To» icity	ticity to fish (Chronic tox-	:	NOEC: > 1 - 10 µ Remarks: Based	g/l on data from similar materials	
aqu	cicity to daphnia and other atic invertebrates (Chron- pxicity)			g/l on data from similar materials	
	actor (Chronic aquatic city)	:	10		
12.2 Pe	sistence and degradabil	ity			
	<u>mponents:</u> anol:				
	degradability	:	Result: Readily bi Biodegradation: 8 Exposure time: 20	84 % [˜]	



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
	a n-2-ol: egradability	: Result: rapidly o	degradable
12.3 Bioa	ccumulative potentia	I	
Ethai Partit octan Prop Partit	ponents: nol: ion coefficient: n- iol/water an-2-ol: ion coefficient: n- iol/water	: log Pow: -0.35 : log Pow: 0.05	
	lity in soil		
12.5 Resu	ata available I lts of PBT and vPvB elevant	assessment	
12.6 Othe	r adverse effects ata available		

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Contaminated packaging	 Dispose of as unused product. Empty containers should be taken to an approved waste han- dling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1987
ADR	: UN 1987
RID	: UN 1987
IMDG	: UN 1987
ΙΑΤΑ	: UN 1987



Version Revision Date: 2.0 03.06.2015	MSDS Number:Date of last issue: 10.03.201547574-00005Date of first issue: 13.01.2015		
14.2 UN proper shipping name			
ADN	: ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)		
ADR	: ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)		
RID	: ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)		
IMDG II	: ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)		
ΙΑΤΑ	: Alcohols, n.o.s. (Ethanol, Propan-2-ol)		
14.3 Transport hazard class(es)		
ADN	: 3		
ADR	: 3		
RID	: 3		
IMDG	: 3		
ΙΑΤΑ	: 3		
14.4 Packing group			
ADN Packing group Classification Code Hazard Identification Number Labels ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code RID Packing group Classification Code Hazard Identification Number Labels IMDG Packing group Labels EmS Code IATA Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	: 3 : III : F1 : 30 : 3 : (D/E) : III : F1 : 30 : 57 : 5		



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
	ng group	: III	
Label 14.5 Envir	s onmental hazards	: Flammable Lic	Juids
ADN Enviro	onmentally hazardous	: no	
ADR Environmentally hazardous		: no	
RID Enviro	onmentally hazardous	: no	
IMDG Marin	e pollutant	: no	
-	ial precautions for use	er	
14.7 Trans Rema	-	-	ARPOL 73/78 and the IBC Code for product as supplied.
SECTION	I 15: Regulatory info	ormation	

Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals		Not applicable		
REACH - Candidate List of Subs Concern for Authorisation (Articl		Not applicable		
Regulation (EC) No 1005/2009 of plete the ozone layer	on substances that de- :	Not applicable		
Regulation (EC) No 850/2004 on persistent organic pol- : Not applicable lutants				
Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major- accident hazards involving dangerous substances				
6	Flammable.	Quantity 1 5,000 t	Quantity 2 50,000 t	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS 5,000 t 50,000 t				
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including ju fuels), (c) gas oils (includ- ing diesel fuels, home heating oils and gas oil		25,000 t	



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
		blending stream heavy fuel oils tive fuels servin purposes and properties as re flammability ar mental hazards products referr points (a) to (d	(e) alterna- ng the same with similar egards id environ- s as the ed to in
Volat	ile organic compounds	emissions (inte	75/EU of 24 November 2010 on industrial egrated pollution prevention and control) c compounds (VOC) content: < 75 %
The components of this product are reported in the following inventories:			

AICS	: All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of R-Phrases			
R11 :	Highly flammable.		
R22 :	Harmful if swallowed.		
R36 :	Irritating to eyes.		
R50/53 :	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.		
R67 :	Vapours may cause drowsiness and dizziness.		
Full text of H-Statements			
H225 :	Highly flammable liquid and vapour.		
H302 :	Harmful if swallowed.		
H319 :	Causes serious eye irritation.		
	May cause drowsiness or dizziness.		
	Very toxic to aquatic life.		
H410 :	Very toxic to aquatic life with long lasting effects.		
Full text of other abbreviations			
Acute Tox. :	Acute toxicity		
Aquatic Acute :	Acute aquatic toxicity		
Aquatic Chronic :	Chronic aquatic toxicity		
Eye Irrit. :	Eye irritation		
Flam. Liq. :	Flammable liquids		
STOT SE :	Specific target organ toxicity - single exposure		



Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005		Date of last issue: 10.03.2015 Date of first issue: 13.01.2015	
IE O	EL	: Ireland. List of Che Limit Values - Sch		emical Agents and Occupational Exposure nedule 1	
IE O	IE OEL / OELV - 8 hrs (TWA) IE OEL / OELV - 15 min (STEL)		 Occupational exposure limit value (8-hour reference period) Occupational exposure limit value (15-minute reference period) 		
Furt	her information				
	rces of key data used to pile the Safety Data et	:		data, data from raw material SDSs, OECD arch results and European Chemicals Agen- ropa.eu/	

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN