# G84-4100

Compact Keyboard

This high-quality compact keyboard is designed for all applications where reliability, reduced space requirements and low weight are of great importance. Useful in e.g. banking/financial transactions, medical facilities and for portable systems. Equally suitable for 19 inch rack-mounted drawers. It can be enhanced with the numerical keypad G84-4700.



# **Key Benefits**

- Single keys with Gold Crosspoint contacts (Cherry MY Modules)
- Designed for continuous use more than 20 Mio. keypresses
- Robust and reliable with precise key actuation
- Space-efficient dimensions
- Lightweight •
- 83- or 86- key layout with full • functionality of a standard keyboard
- Usable with standard drivers of the operating system
- Combo (USB-PS/2) or PS/2 version
- Also available without housing for OEM

# Agency Approvals

CE, VDE/ÜG (EN60950), cURus, FCC DoC CI. B, VCCI CI. 2, BSMI, C-Tick

System Requirements USB or PS/2 connection

#### **Delivery Volume**

Keyboard, Manual, USB-PS/2 adapter (with Combo version)

# **Technical Data**

## Interface

Combo version: USB or PS/2 PS/2 version:

(PS/2 via adapter) PS/2 connection

#### Cable length approx. 1.75 m

Number of keys

86 = with Windows<sup>™</sup> keys 83 = without Windows<sup>TM</sup> keys

## Lifetime of Single Keys

> 50 million keypresses

## Weight

approx. 400 g (without packaging) approx. 500 g (with packaging)

### Dimensions

Keyboard: Width: 282 mm (11.1")

Depth: 132 mm ( 5.2") Height: 27 mm (1.1")

Width: 285 mm (11.2") Packaging: Depth: 135 mm ( 5.3") Height: 30 mm (1.2")

#### **Current Input**

Combo version: max. 100 mA PS/2 version: max. 10 mA

## Reliability

MCBF >  $10^9$  operations MTBF > 90.000 hours

**Storage Temperature** -25 ℃ to 65 ℃

**Operating Temperature** 0 °C to 50 °C

**Packaging Unit** 42 keyboards per master carton 336 keyboards per pallet

Warranty 2 years



# **Order Description**

Order Number	Number of Keys	Colour	Interface
G84-4100LCMxx-0	86	light grey	Combo (USB - PS/2)
G84-4100PTMxx	86	black	Combo (USB - PS/2)
G84-4100LPMxx-0	86	light grey	PS/2
G84-4100PRMxx	86	black	PS/2
G84-4100LCAxx-0	83	light grey	Combo (USB - PS/2)
G84-4100PTAxx	83	black	Combo (USB - PS/2)
G84-4100LPAxx-0	83	light grey	PS/2
G84-4100PRAxx	83	black	PS/2

The xx in the order number defines the country version:

- BE Belgium
- CH Switzerland
- DE Germany
- DK Denmark
- ES Spain
- EU US English / international with €
- FR France
- GB English (UK)
- IT Italy
- NO Norway
- PO Portugal
- SF Sweden/Finland US US-English

Other country versions upon request.

Cherry GmbH Cherrystraße 91275 Auerbach/Opf. Germany Phone: +49 9643 18 0 Internet: www.cherry.de

 Sales:
 +49 1805 243779 (+49 1805 CHERRY)

 E-Mail:
 sales@cherry.de

 Fax:
 +49 9643 18 1545

The manufacturer accepts no liability for errors or nonavailability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2005 Cherry GmbH, Last update: Nov 22, 2005

