

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

Loctite Wood Glue

SDS No. : 661897 V001.0 Revision: 13.05.2019 printing date: 21.10.2020 Replaces version from: -

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1. Product identifier** Loctite Wood Glue
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use:

Wood adhesive, dispersion

**1.3. Details of the supplier of the safety data sheet** Henkel Ltd

Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

### **1.4. Emergency telephone number**

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY-Email: technical.services@henkel.co.uk

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

```
Classification (CLP):
```

Serious eye irritation H319 Causes serious eye irritation.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

Hazard statement:

H319 Causes serious eye irritation.

Category 2

Supplemental information	Contains preservative(s): Isothiazolinone mixture 3:1 (CIT/MIT). May produce an allergic reaction. Contains 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.
Precautionary statement:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.
Precautionary statement: Prevention	P262 Do not get in eyes, on skin, or on clothing. P280 Wear protective gloves/eye protection.
Precautionary statement: Response	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## 2.3. Other hazards

None if used properly. Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

General chemical description: Dispersion adhesive, water-based Base substances of preparation: Polyvinyl acetate dispersion

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Aluminum chloride, basic	215-477-2	1-< 3%	Eye Dam. 1
1327-41-9	01-2119531563-43		H318
			Met. Corr. 1
			H290
1,2-Benzisothiazol-3(2H)-one	220-120-9	0,005-< 0,05 %	Aquatic Acute 1
2634-33-5	01-2120761540-60	( 50 ppm- < 500 ppm)	H400
			Aquatic Chronic 1
			H410
			Acute Tox. 4; Oral
			H302
			Skin Irrit. 2
			H315
			Skin Sens. 1
			H317
			Eye Dam. 1
			H318
			Acute Tox. 2
			H330
Isothiazolinone mixture 3:1 (CIT/MIT)	01-2120764691-48	0,0001-< 0,0015	Acute Tox. 2; Inhalation
55965-84-9	01 2120/01091 10	%	H330
		(1 ppm- < 15 ppm)	Aquatic Chronic 1
			H410
			Acute Tox. 3; Oral
			H301
			Acute Tox. 2; Dermal
			H310
			Eye Dam. 1
			H318
			Skin Sens. 1A
			H317
			Aquatic Acute 1
			H400
			Skin Corr. 1C
			H314
			M factor (Acute Aquat Tox): 100 M factor
			(Chron Aquat Tox): 100
	1	I	(Chion Figure Font): 100

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

General information: In case of adverse health effects seek medical advice.

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

**Suitable extinguishing media:** carbon dioxide, foam, powder, water spray jet, fine water spray

## Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus. Wear protective equipment.

### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures Wear protective equipment.Danger of slipping on spilled product.Ensure adequate ventilation.Avoid contact with skin and eyes.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust). Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated. Avoid skin and eye contact.

Hygiene measures: Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container. Store in a cool, dry place. Temperatures between 0 °C and + 30 °C Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Wood adhesive, dispersion

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Occupational Exposure Limits**

### Valid for

Great Britain

Ingredient [Regulated substance]	ррт	mg/m <sup>3</sup>	~ 1	Short term exposure limit category / Remarks	Regulatory list
Aluminum chloride, basic		2	Time Weighted Average		EH40 WEL
1327-41-9			(TWA):		
[ALUMINIUM SALTS, SOLUBLE]					

## **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ррт	mg/m <sup>3</sup>	~ 1	Short term exposure limit category / Remarks	Regulatory list
Aluminum chloride, basic		2	Time Weighted Average		IR_OEL
1327-41-9			(TWA):		
[ALUMINIUM SALTS, SOLUBLE]					

## Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	Compartment	periou	mg/l	ppm	mg/kg	others	
Aluminum chloride, basic 1327-41-9	aqua (freshwater)		0,0003 mg/l		8 8		
Aluminum chloride, basic 1327-41-9	aqua (marine water)		0,00003 mg/l				
Aluminum chloride, basic 1327-41-9	aqua (intermittent releases)		20 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (freshwater)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (marine water)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sewage treatment plant (STP)		0,23 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (freshwater)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (marine water)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Soil				0,01 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (intermittent releases)		0,0039 mg/l				

### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Aluminum chloride, basic 1327-41-9	Workers	inhalation	Long term exposure - systemic effects		20,2 mg/m3	
Aluminum chloride, basic 1327-41-9	General population	oral	Long term exposure - systemic effects		3,4 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	oral	Long term exposure - systemic effects		0,09 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Respiratory protection: Suitable breathing mask when there is inadequate ventilation. Combination filter: ABEKP (EN 14387) This recommendation should be matched to local conditions.

Hand protection: In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.1 mm Perforation time > 480 minutes In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than

those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection: Goggles which can be tightly sealed. Protective eye equipment should conform to EN166.

Skin protection: Suitable protective clothing Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts. Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

#### **SECTION 9: Physical and chemical properties**

#### **9.1. Information on basic physical and chemical properties** Appearance liquid

Odor Odour threshold	free-flowing white little intrinsic odour No data available / Not applicable
pH (20 °C (68 °F))	2,8 - 3,6
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	Not applicable
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable

No data available / Not applicable 1,06 - 1,10 g/cm3

No data available / Not applicable No data available / Not applicable Miscible

No data available / Not applicable No data available / Not applicable No data available / Not applicable 9.000 - 15.000 mPa.s

No data available / Not applicable No data available / Not applicable No data available / Not applicable

9.2. Other information

Viscosity (kinematic)

Explosive properties

Oxidising properties

Explosive limits

Vapour pressure

Density

Solubility

Viscosity

Relative vapour density:

(20 °C (68 °F)) Bulk density

Solubility (qualitative)

Auto-ignition temperature

Decomposition temperature

(Brookfield; 23 °C (73.4 °F))

No data available / Not applicable

(23 °C (73.4 °F); Solvent: Water) Partition coefficient: n-octanol/water

### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

None if used for intended purpose.

**10.2. Chemical stability** Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

**10.4. Conditions to avoid** None if used for intended purpose.

**10.5. Incompatible materials** None if used properly.

**10.6. Hazardous decomposition products** None known.

## **SECTION 11: Toxicological information**

### General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

#### 11.1. Information on toxicological effects

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Aluminum chloride, basic 1327-41-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
1,2-Benzisothiazol-3(2H)-	LD50	490 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
one				Toxicity)
2634-33-5				
Isothiazolinone mixture	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
3:1 (CIT/MIT)				
55965-84-9				

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Aluminum chloride, basic 1327-41-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

#### Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Aluminum chloride, basic	LC50	> 5 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
1327-41-9						Inhalation Toxicity)
1,2-Benzisothiazol-3(2H)-	LC50	0,4 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
one		-				Inhalation Toxicity)
2634-33-5						-
Isothiazolinone mixture	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
3:1 (CIT/MIT)		-				Inhalation Toxicity)
55965-84-9						

#### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Aluminum chloride, basic 1327-41-9	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

## Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Aluminum chloride, basic	highly			not specified
1327-41-9	corrosive			
Aluminum chloride, basic	slightly		rabbit	not specified
1327-41-9	irritating			
Aluminum chloride, basic	Category 1	1 s	rabbit	not specified
1327-41-9	(irreversible			
	effects on the			
	eye)			
1,2-Benzisothiazol-3(2H)-	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)
one				
2634-33-5				
Isothiazolinone mixture	Category 1		rabbit	not specified
3:1 (CIT/MIT)	(irreversible			
55965-84-9	effects on the			
	eye)			

### Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

## Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

## Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components	Result	Route of	Exposure	Species	Sex	Method
CAS-No.		application	time /			
			Frequency			
			of treatment			
Isothiazolinone mixture	not carcinogenic	oral: drinking	2 y	rat	male/female	OECD Guideline 453
3:1 (CIT/MIT)		water	daily			(Combined Chronic
55965-84-9						Toxicity /
						Carcinogenicity
						Studies)

## **Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL P 112 mg/kg NOAEL F1 56,6 mg/kg NOAEL F2 56,6 mg/kg	Two generation study	oral: feed	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

### STOT-single exposure:

No data available.

## STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
1,2-Benzisothiazol-3(2H)-	NOAEL 150 mg/kg	oral: gavage	28 days	rat	OECD Guideline 407
one			daily		(Repeated Dose 28-Day
2634-33-5					Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)-	NOAEL 69 mg/kg	oral: feed	90 days	rat	EPA OPP 82-1 (90-Day
one			daily		Oral Toxicity)
2634-33-5					
Isothiazolinone mixture	NOAEL 16,3 mg/kg	oral:	90 d	rat	OECD Guideline 408
3:1 (CIT/MIT)		drinking	daily		(Repeated Dose 90-Day
55965-84-9		water			Oral Toxicity in Rodents)
Isothiazolinone mixture	NOAEL 0.34 mg/m3	inhalation:	90 d	rat	OECD Guideline 413
3:1 (CIT/MIT)		aerosol	6 h/d, 5 d/w		(Subchronic Inhalation
55965-84-9					Toxicity: 90-Day)
Isothiazolinone mixture	NOAEL 2,625 mg/kg	dermal	90 d	rat	EPA OPP 82-3
3:1 (CIT/MIT)			6 h/d		(Subchronic Dermal
55965-84-9					Toxicity 90 Days)

#### Aspiration hazard:

No data available.

## **SECTION 12: Ecological information**

### General ecological information:

Do not empty into drains, soil or bodies of water.

### 12.1. Toxicity

### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Aluminum chloride, basic	LC50	> 1.000 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
1327-41-9				Danio rerio)	Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
2634-33-5					Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish,
2634-33-5					Juvenile Growth Test)
Isothiazolinone mixture 3:1	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
(CIT/MIT)					Acute Toxicity Test)
55965-84-9					
Isothiazolinone mixture 3:1	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
(CIT/MIT)					early lite stage toxicity test)
55965-84-9					

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Aluminum chloride, basic	EC50	98 mg/l	48 h	Daphnia magna	OECD Guideline 202
1327-41-9					(Daphnia sp. Acute
					Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202
2634-33-5					(Daphnia sp. Acute
					Immobilisation Test)
Isothiazolinone mixture 3:1	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202
(CIT/MIT)					(Daphnia sp. Acute
55965-84-9					Immobilisation Test)

### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

GLG M	Value type	Value	Exposure time	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	1,2 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,0036 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Aluminum chloride, basic 1327-41-9	EC50	1,5 - 2 mg/l	96 h	Scenedesmus quadricauda	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,11 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,0403 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
1,2-Benzisothiazol-3(2H)-one	EC50	23 mg/l	3 h	activated sludge of a	OECD Guideline 209
2634-33-5				predominantly domestic sewage	(Activated Sludge,
					Respiration Inhibition Test)
Isothiazolinone mixture 3:1	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209
(CIT/MIT)					(Activated Sludge,
55965-84-9					Respiration Inhibition Test)

### 12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	not readily biodegradable.	aerobic	42,1 %	28 d	other guideline:
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

## 12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 day		not specified	other guideline:
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

## 12.4. Mobility in soil

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Aluminum chloride, basic	< 3		not specified
1327-41-9			
1,2-Benzisothiazol-3(2H)-one	0,7	20 °C	EU Method A.8 (Partition Coefficient)
2634-33-5			
Isothiazolinone mixture 3:1	-0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
(CIT/MIT)			Method)
55965-84-9			

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Aluminum chloride, basic	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not
1327-41-9	be conducted for inorganic substances.
1,2-Benzisothiazol-3(2H)-one	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2634-33-5	Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture 3:1 (CIT/MIT)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
55965-84-9	Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

#### Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080409

# **SECTION 14: Transport information** 14.1. UN number Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.2. UN proper shipping name Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.3. Transport hazard class(es) Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.4. Packing group Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.5. **Environmental hazards** Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.6. Special precautions for user Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

0.0 %

VOC content

(VOCV 814.018 VOC regulation CH)

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.