

SAFETY DATA SHEET EASY STRIP

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EASY STRIP

Product number A141 EV

Internal identification Janitorial

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Floor Polish Remover.

1.3. Details of the supplier of the safety data sheet

Supplier Evans Vanodine Europe

6-9 Trinity Street, Dublin 2.

D02 EY47.

Republic of Ireland.

Manufacturer Evans Vanodine International plc

Brierley Road Walton Summit Preston. UK. PR5 8AH Tel: 01772 322 200

 $e\hbox{-}mail: product compliance @evans vano dine.co.uk\\$

1.4. Emergency telephone number

Emergency telephone New Safety Data Sheets - 01772 322 200 - Mon to Thur. 8.30am to 4.30pm - Fri 8.30am to

1.30 pm (Also available 24/7 from our website www.evansvanodine.co.uk) For Technical Advice about this SDS - 01772 318 818 - Mon to Thur 8.30 am to 4.45 pm - Fri 8.30 am to

1.30pm

National emergency telephone For Health Care Professionals only -

number For use in UK: Contact the National Poisons Information Service for further advice.

For use in the Republic of Ireland: To report a poisoning incident contact The National

Poisons Information Centre, Beaumont Hospital, Dublin (01-8092166). .

For use in Malta: Emergency services (Ambulance, Fire and Rescue, Police): 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

EASY STRIP

Hazard pictograms





Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Precautionary statements P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P315 Get immediate medical advice/ attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with local regulations.

Contains 2-AMINOETHANOL

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| 2-BUTOXYETHANOL | | 15-20% |
|----------------------|----------------------|--------|
| CAS number: 111-76-2 | EC number: 203-905-0 | |
| Classification | | |
| Acute Tox. 4 - H302 | | |
| Acute Tox. 4 - H312 | | |
| Acute Tox. 4 - H332 | | |
| Skin Irrit. 2 - H315 | | |
| Eye Irrit. 2 - H319 | | |

EASY STRIP

2-AMINOETHANOL 5-10%

CAS number: 141-43-5 EC number: 205-483-3 REACH registration number: 01-

2119486455-28

Spec Conc Limits :- STOT SE 3 (H335) ≥ 5%

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Corr. 1B - H314

Eye Dam. 1 - H318

STOT SE 3 - H335

Aquatic Chronic 3 - H412

1-AMINOPROPAN-2-OL 3-5%

CAS number: 78-96-6 EC number: 201-162-7

Classification

Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318

TETRA SODIUM ETHYLENE DIAMINE TETRA ACETATE

1-3%

CAS number: 64-02-8 EC number: 200-573-9

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H332

Eye Dam. 1 - H318

ALCOHOL (C9-11) ETHOXYLATE (8EO)

0.1-1%

CAS number: 68439-46-3

Alternative CAS No 68439-45-2

Classification

Acute Tox. 4 - H302 Eye Dam. 1 - H318

SODIUM (C12-14) ALKYL ETHOXY SULPHATE

0.1-1%

CAS number: 68891-38-3 EC number: 500-234-8 REACH registration number: 01-

2119488639-16-0020

Spec Conc Limits :- Eye Dam. 1 (H318) >=30%, Eye Irrit. 2 (H319) >10% <30%, NC (Not Classified) <=10%

Classification

Skin Irrit. 2 - H315

Eye Dam. 1 - H318 Aquatic Chronic 3 - H412

EASY STRIP

2-PROPENOIC ACID, METHYL ESTER, REACTION PRODUCTS WITH 2-ETHYL-1-HEXANAMINE & SODIUM

0.1-1%

HYDROXIDE

CAS number: 68610-44-6 EC number: 271-865-1

Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318

SODIUM HYDROXIDE <0.1%

CAS number: 1310-73-2 EC number: 215-185-5 REACH registration number: 01-

2119457892-27-xxxx

Spec Conc Limits: - Skin Corr. 1A (H314) >= 5 %, Skin Corr. 1B (H314) >=2% <5 %, Skin Irrit. 2 (H315) >=0.5%<2%, Eye

Irrit. 2 (H319) >= 0.5% < 2%

Classification

Met. Corr. 1 - H290 Skin Corr. 1A - H314 Eye Dam. 1 - H318

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get

medical attention immediately.

Skin contact Wash with plenty of water. Get medical attention promptly if symptoms occur after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Irritation of nose, throat and airway.

Ingestion May cause chemical burns in mouth and throat.

Skin contact Burning pain and severe corrosive skin damage. May cause serious chemical burns to the

skin.

Eye contact Severe irritation, burning and tearing. Prolonged contact causes serious eye and tissue

damage.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

EASY STRIP

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazardsThermal decomposition or combustion products may include the following substances:

Irritating gases or vapours.

5.3. Advice for firefighters

for firefighters

Special protective equipment

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing, gloves, eye and face protection. For personal protection, see

Section 8.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the

Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Small Spillages: Flush away spillage with plenty of water. Large Spillages: Contain and

absorb spillage with sand, earth or other non-combustible material. Collect and place in

suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing, gloves, eye and face protection. Avoid breathing vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container in a cool, well-ventilated place. Store away from the

following materials: Oxidising materials. & Acids.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description See Product Information Sheet & Label for detailed use of this product.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³ Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³ St.

2-AMINOETHANOL

Long-term exposure limit (8-hour TWA): WEL 1 ppm 2.5 mg/m³ Short-term exposure limit (15-minute): WEL 3 ppm 7.6 mg/m³ Sk

SODIUM HYDROXIDE

EASY STRIP

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit. Sk = Can be absorbed through skin. Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

This product must not be handled in a confined space without adequate ventilation.

Eye/face protection The following protection should be worn: Chemical splash goggles or face shield.

Hand protection Wear protective gloves. (Household rubber gloves.)

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection Respiratory protection not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Clear. Colourless.

Odour Slight. Glycol ether.

pH (concentrated solution): 12.00

Melting point -2°C

Initial boiling point and range 102°C @ 760 mm Hg

Flash point Boils without flashing.

Relative density 1.005 @ 20°C

Solubility(ies) Soluble in water.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Reactions with the following materials may generate heat: Strong acids.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous

See sections 10.1,10.4 & 10.5

reactions

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

EASY STRIP

10.5. Incompatible materials

Materials to avoid Strong acids. Aluminium, Tin, Zinc and their alloys.

10.6. Hazardous decomposition products

Hazardous decomposition

products

When heated, vapours/gases hazardous to health may be formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects We have not carried out any animal testing for this product. Any ATE figures quoted below are

from Toxicity Classifications that have been carried out using ATE (Acute Toxicity Estimate) Calculation Method using LD50 or ATE figures provided by the Raw Material Manufacturer.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 5,174.48

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 4,023.57

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 44.97

ATE inhalation (dusts/mists

mg/l)

155.91

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity We have not carried out any Aquatic testing, therefore we have no Aquatic Toxicity Data

specifically for this product. The Aquatic Toxicity Data, where provided by the raw material manufacturer for ingredients with aquatic toxicity, can be made available on request.

12.2. Persistence and degradability

Persistence and degradability This product, at use dilutions, is readily broken down in biological effluent treatment plants.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

EASY STRIP

13.1. Waste treatment methods

Disposal methods Discharge used solutions to drain. Small amounts (less than 5 Litres) of unwanted product

may be flushed with water to sewer. Larger volumes must be sent for disposal as special

waste. Rinse out empty container with water and consign to normal waste.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3267 UN No. (IMDG) 3267 UN No. (ICAO) 3267

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ethanolamine)

Proper shipping name (IMDG) CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ethanolamine)

Proper shipping name (ICAO) CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ethanolamine)

14.3. Transport hazard class(es)

ADR/RID class Class 8 : Corrosive Substances

ADR/RID label 8

IMDG class

Class 8: Corrosive substances.

ICAO class/division

Class 8: Corrosive substances.

Transport labels



14.4. Packing group

ADR/RID packing group II
IMDG packing group II
ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-A, S-B

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not relevant. for a packaged product.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EASY STRIP

EU legislation Safety Data Sheet prepared in accordance with REACH Commission Regulation (EU) No

2015/830 (which amends Regulation (EC) No 453/2010 & 1907/2006).

The product is as classified under GHS/CLP- Regulation (EC) No 1272/2008 classification,

labelling & packaging of substances & mixtures.

Ingredients are listed with classification under GHS/CLP - Regulation (EC) No 1272/2008

classification, labelling & packaging of substances & mixtures.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out as not applicable as this product is a mixture.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

ATE: Acute Toxicity Estimate.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

IMDG: International Maritime Dangerous Goods.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

GHS: Globally Harmonized System.

Spec Conc Limits = Specific Concentration Limits.

Classification abbreviations

and acronyms

Acute Tox. = Acute toxicity

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation

Met. Corr. = Corrosive to metals Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation

STOT SE = Specific target organ toxicity-single exposure

Key literature references and

sources for data

Material Safety Data Sheet, Miscellaneous manufacturers. CLP Class - Table 3.1 List of harmonised classification and labelling of hazardous substances. ECHA - C&L Inventory

database.

Classification procedures according to Regulation (EC)

1272/2008

Calculation Method.

Revision comments Change of Address. & Addition of national emergency telephone number.

Revision date 14/01/2021

Revision 10

SDS status The Hazard Statements listed below in this Section No 16 relate to the Raw Materials

(Ingredients) in the Product (as listed in Section 3) and NOT the product itself. For the Hazard

Statements relating to this Product see Section 2.

EASY STRIP

Hazard statements in full H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.