

SAFETY DATA SHEET CLEENOL THICK BLEACH.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CLEENOL THICK BLEACH.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd

Neville House Beaumont Road

Banbury

Oxon OX16 1RB

UK

Tel: +44 (0)1295 251721 Fax: +44 (0)1295 269561 sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone Emergency contact number 01295 251721 (9am to 5pm Monday to Friday excluding bank

holidays). Ask for Technical Department quoting the product name. Outside of these hours please contact your doctor or local hospital accident and emergency department or the NHS enquiry service (dial 111) quoting product name and present this MSDS advising them that

the product is registered with the National Poisons Information Service

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Environmental hazards Not Classified

Classification (67/548/EEC or Xi;R36/38. R31.

1999/45/EC)

2.2. Label elements

Pictogram



Signal word Danger

CLEENOL THICK BLEACH.

Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves. P280 Wear eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P102 Keep out of reach of children.

Supplemental label

EUH206 Warning! Do not use together with other products. May release dangerous gases

information (chlorine).

Contains SODIUM HYPOCHLORITE SOLUTION, ... % CI ACTIVE

2.3. Other hazards

Other Hazards None

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SODIUM HYPOCHLORITE SOLUTION, 1-5%

CAS number: 7681-52-9 EC number: 231-668-3 REACH registration number: 01-

2119488154-34-XXXX

M factor (Acute) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Corr. 1B - H314 C;R34 R31 N;R50

Eye Dam. 1 - H318 Aquatic Acute 1 - H400

SODIUM LAURYL ETHER SULPHATE 1-5%

CAS number: 3088-31-1 EC number: 221-416-0 REACH registration number: 01-

2119488639-16-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 Xi;R36/38.

Eye Irrit. 2 - H319

SODIUM HYDROXIDE <1%

CAS number: 1310-73-2 EC number: 215-185-5 REACH registration number: 01-

2119457892-27-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Corr. 1A - H314 C;R35

Eye Dam. 1 - H318

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

CLEENOL THICK BLEACH.

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause respiratory irritation.

Ingestion May cause discomfort if swallowed.

Skin contact May cause skin irritation.

Eye contact May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments Seek medical attention if irritation or symptoms persist. Symptomatic treatment

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Burning may produce irritating, toxic and obnoxious fumes.

Oxides of Carbon, Nitrogen and Sulphur.

5.3. Advice for firefighters

Special protective equipment

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

for firefighters clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections See section 3,8 & 13 for further information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

CLEENOL THICK BLEACH.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in

the original container.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

SODIUM HYDROXIDE

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment





Appropriate engineering

Eye/face protection

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

1

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. The following protection should be worn: Chemical

splash goggles or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves

should comply with European Standard EN374.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measuresDo not smoke in work area. Wash at the end of each work shift and before eating, smoking

and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

CLEENOL THICK BLEACH.

ReactivityNo test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Contact with acids liberates toxic gas.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Irritating to respiratory system.

Ingestion May cause discomfort if swallowed.

Skin contact Irritating to skin.

Eye contact Irritating to eyes.

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Very toxic to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

CLEENOL THICK BLEACH.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General As supplied, this product is consigned under the Limited Quantities provisions.

14.1. UN number

UN No. (ADR/RID) 1760 UN No. (IMDG) 1760

UN No. (ICAO) 1760

UN No. (ADN) 1760

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, AMINES, C12-14 -

ALKYLDIMETHYL, N-OXIDES

Proper shipping name (IMDG) CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, AMINES, C12-14 -

ALKYLDIMETHYL, N-OXIDES, 2-TERT-BUTYLCYCLOHEXYL ACETATE,

BENZOPHENONE)

Proper shipping name (ICAO)

CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, AMINES, C12-14 -

ALKYLDIMETHYL, N-OXIDES

Proper shipping name (ADN)

CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, AMINES, C12-14 -

ALKYLDIMETHYL, N-OXIDES

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID classification code C9

ADR/RID label 8

IMDG class 8

ICAO class/division 8

ADN class 8

Transport labels



14.4. Packing group

ADR/RID packing group Ш IMDG packing group Ш

ADN packing group Ш

ICAO packing group Ш

14.5. Environmental hazards

CLEENOL THICK BLEACH.

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-B

ADR transport category 3

Emergency Action Code 2X

Hazard Identification Number 80

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance CHIP for everyone HSG228.

Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations

Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 02/04/2019

Revision 15

Supersedes date 05/05/2017

SDS number F3

Risk phrases in full R31 Contact with acids liberates toxic gas.

R34 Causes burns.

R35 Causes severe burns.
R36/38 Irritating to eyes and skin.
R50 Very toxic to aquatic organisms.

CLEENOL THICK BLEACH.

Hazard statements in full H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.