





TEGERA® 8805 INFINITY



Learn more

SUPER SOFT, PALM DIPPED, CUT B GLOVE

Dexterous cut resistant glove, level B, with touchscreen function. Ultra-light thanks to 18 gg knitted with CRF® cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Suitable for precision work. Breathable materials for all day comfort. Protection against contact heat up to 100°C. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Extra comfortable
- Flexible
- Durable
- Good grip in oily environments

FUNCTIONS

- Withstands contact heat up to 100°C
- For touchscreen
- Approved for handling foodstuffs
- Anatomically designed
- Reinforcement between index finger and thumb















PREVENTS RISK OF

cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE

dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

fine assembly, assembly, machine operating, building and construction, carpentry, painting, installation work, hvac installation, sheet-metal work, engineering, transport work, machine driving, warehouse work, airport work, metalwork, glass industry work, repair work, paper industry work, service work, shop work

PRIMARY INDUSTRIES OF USE

pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING MATERIAL 18 gg, Carbon, CRF® Technology, Nylon,

Stainless steel fibre yarn

GRIP DESIGN Foam grip pattern

COLOUR Grey, Yellow

PAIRS PER: BUNDLE/CARTON 6/120

DISPLAY TYPE Bulk pack

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13977) TDM: 9 N

INNER MATERIAL SPECIFICATION Nylon, HPPE, Stainless steel

fibre yarn, Carbon thread

OUTER MATERIAL SPECIFICATION Nitrile







EN 420:2003 +A1:2009





*	EN 407:2004 X1XXXX



SIZE	ARTICLE NUMBER	EAN
5	8805-5	7340118328089
6	8805-6	7340118319322
7	8805-7	7340118319339
8	8805-8	7340118319346
9	8805-9	7340118319353
10	8805-10	7340118319308
11	8805-11	7340118319315



 $Limavägen 28, SE-793 32 \ Leksand, Sweden Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com | or$